

MS434091

GC FUJI I LIQUID MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

DISTRIBUTOR

GC AMERICA INC. 3737 West 127th St. Alsip, Illinois, 60803 Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

COMMON NAME: GC FUJI I LIQUID

GC FUJI I CAPSULES LIQUID

CHEMICAL NAME: N.A.

PRODUCT USE: Dental luting cement material - liquid component

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT	C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Distilled water	7732-18-5	N.E.	N.E.	50-55
Polyacrylic acid	9003-01-4	TWA=10ppm	LD5O = 2500 mg/kg	30-40
		(ACGIH)	(oral rat)	
			LC50=N.E.	

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.

APPEARANCE AND ODOR: Colorless, slightly viscous and odorless liquid

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: Not flammable FLAMMABLE LIMITS: N.A.

EXTINGUISHING MEDIA: Alcohol foam

SPECIAL FIRE FIGHTING PROCEDURES: Full protective clothing and self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS COMBUSTION PRODUCTS: Emits acrid smoke when heated beyond boiling point.

SECTION 5 - REACTIVITY DATA

STABILITY:	Stable 🛚	Unstable
POLYMERIZATION:	Will Not Occur 🔀	Will Occur

CONDITIONS TO AVOID: High heat

INCOMPATIBILITY (Materials to Avoid): Alkali will inactivate product

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: $\ensuremath{N.E.}$



GC FUJI I LIQUID MS434091

Page 2 of 2 SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS		X						
TERATOGENIC AFFECTS		X						
REPRODUCTIVE TOXIN		X						
CARCINOGENICITY		X						
SENSITIZER		X						

Skin 🖂 Inhalation Ingestion X **ROUTES OF ENTRY:**

HEALTH HAZARD (Acute and Chronic): Acidic solution (pH=1.90), care should be taken to avoid contact with skin or eyes.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: N.E.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

EMERGENCY FIRST AID PROCEDURES:

INGESTION: Do not induce vomiting - give large volumes of water. Seek medical attention.

SKIN: Wash with soap and water. If irritation develops seek medical attention.

EYES: Flush with water for 15 minutes. If irritation develops seek medical attention.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

WASTE DISPOSAL METHOD: Dilute with water and flush into drain with large volumes of water.

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS: Store in a cool dry place in tightly closed container.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: None required

Mechanical: N.A. **VENTILATION:** Local Exhaust: N.A. Special: N.E. Other: N.A.

PROTECTIVE GLOVES: Latex gloves are recommended

EYE PROTECTION: Goggles or full face shield

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Do not spill on clothing. Eyewash station

WORK/HYGIENIC PRACTICE: N.E.

SECTION 9- PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

DATE: 16 May 2006

REVISED: 23 September 2009 **REVIEWED:** 09 March 2012

.....

N.A. = NOT APPLICABLEN.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

.....

NFPA

FIRE - 0 TOXICITY - 1 **REACTIVITY - 0** SPECIAL - ACID