

MS434001

GC FUJI I - POWDER MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

DISTRIBUTOR

GC AMERICA INC. 3737 West 127th St. Alsip, Illinois, 60803 Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

COMMON NAME: GC FUJI I - POWDER

GC FUJI I CAPSULES - POWDER

CHEMICAL NAME: N.A.

PRODUCT USE: Dental luting cement material - powder component

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT	C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Alumino-fluoro-silicate glass	Not listed	TLV=10mg/m³	N.E.	95
(amorphous)		PEL=15mg/m³	N.E.	
		(ACGIH)		
Polyacrylic acid	9003-01-4	TWA=10ppm	LD5O = 2500 mg/kg	5
		(ACGIH)	(oral rat)	
			LC50=N.E.	

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT:N.E.SPECIFIC GRAVITY (H2O = 1):2.56VAPOR PRESSURE:N.A.MELTING POINT: 1350° CVAPOR DENSITY:N.A.EVAPORATION RATE:N.A.SOLUBILITY IN WATER:InsolubleODOR THRESHOLD:N.E.

COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E. APPEARANCE AND ODOR: Very fine white powder

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: Not flammable FLAMMABLE LIMITS: N.A.

EXTINGUISHING MEDIA: Alcohol foam

SPECIAL FIRE FIGHTING PROCEDURES: Full protective clothing and self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS COMBUSTION PRODUCTS: Emits acrid smoke when heated above 101°C.

SECTION 5 - REACTIVITY DATA

STABILITY: Stable ☐ Unstable ☐ POLYMERIZATION: Will Not Occur ☐ Will Occur ☐

CONDITIONS TO AVOID: High heat

INCOMPATIBILITY (Materials to Avoid): Alkali will inactivate product

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: No decomposition if used or stored according to specifications.



MS434001 GC FUJI I - POWDER SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

Page 2 of 2

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS		X						
TERATOGENIC AFFECTS		X						
REPRODUCTIVE TOXIN		X						
CARCINOGENICITY		X						
SENSITIZER		X						

ROUTES OF ENTRY: Inhalation 🛛 Skin 🖂 Ingestion 🖂

HEALTH HAZARD (Acute and Chronic): Dusts of silica glass is a known cause of silicosis, a non-cancerous lung disease.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Irritation and soreness in throat and nose.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May aggravate preexisting upper respiratory and lung disease.

EMERGENCY FIRST AID PROCEDURES:

INGESTION: Do not induce vomiting - give large volumes of water. Seek medical attention.

SKIN: Wash with soap and water. If irritation develops seek medical attention. **EYES:** Flush with water for 15 minutes. If irritation develops seek medical attention.

INHALATION: Remove to fresh air, drink water to clear throat and blow nose to evacuate dust.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL: Avoid generating dust during cleanup. If an excessive amount of dust is generated use a filter equipped vacuum and MSHA/NIOSH approved mask.

WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations.

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS: Store at normal room temperatures and humidity.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: Minimize exposure to dust in accordance with good hygiene practices. If needed, use MSHA-NIOSH approved respiration.

VENTILATION: Local Exhaust: Yes Mechanical: YES Special: N.A. Other: N.A.

PROTECTIVE GLOVES: Disposable vinyl gloves are recommended.

EYE PROTECTION: Goggles or full face shield

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Do not spill on clothing. Eyewash station

WORK/HYGIENIC PRACTICE: Follow safe hygiene practices.

SECTION 9- PREPARATION INFORMATION

This data is supplied to comply v	with OSHA Hazard	Communication Standard 29	CFR 1910.1200 and	! W.H.M.I.S. :	CPR

DATE: 16 May 2006
REVISED: 20 February 2012

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

NFPA

FIRE – 0 TOXICITY – 1 REACTIVITY – 0 SPECIAL –